

- 2. WINGWALL BARS CONSISTENTLY REFERENCED FROM END OF WING FOR ALL HEADWALLS.
- 3. TOP TRANSVERSE FLOOR BARS ARE REFERENCED APPROXIMATELY 4"
 FROM THE BACK OF THE PARAPET FOR ALL HEADMALLS.
- 4. THERE ARE NO 5c5 BARS IN THE 3',4',5' AND 6' HEIGHT HEADWALL.
- 5. FOR REINFORCING IN CURTAIN WALL SEE CURTAIN WALL DETAILS THIS DWG.
- 6. FOR DIMENSION TABLE SEE DWG. FWH 0-3-87.
- 7. THERE ARE NO 6m2 BARS IN THE 3' & 4' SPAN HEADWALLS.

| I | 2 | STANDARD DESIGN | | |
|--------------------------|----------------|--|------|------------|
| DATE | 4 | FLARED | WING | HEADWALLS |
| LATEST REVISION 04-07 | Momen C. M. D. | FOR REINFORCEO CONCRETE BOX CULVERTS | | |
| | | IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION | | |
| | | MAY , 1987 | | FWH 0-4-87 |

CURTAIN z

FEVISION - 04-07 - ADDED FWH 0-4-87