VARIABLE DIMENSIONS AND QUANTITIES FOR BARREL SECTIONS

BAR LIST

	a1			a2			b1			b2			e1			e2			f1			f2			k1			k2			k4				k5				k6			k7			k9			m1			m2			m4				m5				m6			m7			m9		
FILL	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	FILL
0	5	12	7'-8	5	4.5	7'-8	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	5	12	21'-11	5	12	8'-1	4	12	4'-10	1'-8	3'-2	5	12	4'-10	1'-8	3'-2	5	12	5'-2	4	4.5	21'-11	4	12	22'-5	5	12	6'-8	5	12	7'-9	1'-7	6'-2	5	12	7'-9	1'-7	6'-2	4	9	22'-5	4	9	3'-10	4	4.5	22'-5	0
1	5	12	7'-9	5	4.5	7'-9	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	5	12	21'-11	5	12	8'-0	4	12	4'-11	1'-9	3'-2	5	12	4'-10	1'-8	3'-2	5	15	17'-8	5	15	4'-8	5	7.5	21'-11	4	12	22'-5	5	12	6'-11	5	12	7'-9	1'-7	6'-2	5	12	22'-5	5	12	3'-11	5	4.5	22'-5	1
2	5	12	7'-5	5	4.5	7'-5	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	5	12	21'-11	6	12	8'-3	5	12	5'-1	2'-1	3'-0	5	12	4'-9	1'-9	3'-0	5	12	16'-7	6	12	5'-5	5	4.5	21'-11	5	12	22'-5	5	12	6'-5	5	12	7'-10	1'-9	6'-1	5	12	7'-8	1'-7	6'-1	5	9	15'-8	5	9	4'-0	5	4.5	22'-5	2
3	4	9	7'-5	4	4.5	7'-5	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	9	21'-11	4	9	6'-7	4	9	4'-9	1'-10	2'-11	4	9	4'-8	1'-9	2'-11	5	12	15'-2	5	12	4'-7	5	4.5	21'-11	4	12	22'-5	5	12	7'-0	4	9	7'-10	1'-9	6'-1	4	9	7'-8	1'-7	6'-1	4	9	15'-0	5	9	4'-6	4	4.5	22'-5	3
4	4	9	7'-5	4	4.5	7'-5	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	12	21'-11	5	12	7'-1	4	9	4'-8	1'-9	2'-11	4	9	4'-8	1'-9	2'-11	5	12	14'-10	5	12	4'-5	5	4.5	21'-11	4	12	22'-5	5	12	6'-11	4	9	7'-10	1'-9	6'-1	4	9	7'-8	1'-7	6'-1	4	9	14'-10	5	9	4'-6	4	4.5	22'-5	4
5-7	4	9	7'-5	4	4.5	7'-5	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	12	21'-11	5	12	7'-0	4	9	4'-8	1'-9	2'-11	4	9	4'-8	1'-9	2'-11	5	12	14'-8	6	12	4'-11	5	4.5	21'-11	4	12	22'-5	5	12	6'-1	4	9	7'-8	1'-7	6'-1	4	9	7'-8	1'-7	6'-1	5	9	14'-8	5	9	3'-11	5	4.5	22'-5	5-7
8-10	5	12	7'-6	4	4.5	7'-6	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	5	12	21'-11	5	12	6'-4	5	12	4'-9	1'-9	3'-0	5	12	4'-9	1'-9	3'-0	6	12	14'-6	6	12	4'-7	6	4.5	21'-11	4	12	22'-5	5	12	6'-11	5	12	7'-11	1'-9	6'-2	5	12	7'-9	1'-7	6'-2	5	9	14'-9	6	9	4'-7	5	4.5	22'-5	8-10
11-13	5	12	7'-9	4	4.5	7'-9	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	5	15	21'-11	6	15	7'-4	5	12	4'-10	1'-9	3'-1	5	12	4'-9	1'-8	3'-1	7	15	14'-8	7	15	4'-9	7	7.5	21'-11	4	9	22'-5	5	9	7'-0	5	12	7'-10	1'-7	6'-3	5	12	7'-10	1'-7	6'-3	7	15	14'-11	7	15	4'-8	7	7.5	22'-5	11-13
14-16	5	12	7'-11	4	4.5	7'-11	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	9	21'-11	5	9	7'-1	5	12	4'-11	1'-9	3'-2	5	12	4'-10	1'-8	3'-2	5	9	14'-7	6	9	4'-11	5	4.5	21'-11	4	9	22'-5	5	9	7'-2	5	12	7'-11	1'-7	6'-4	5	12	7'-11	1'-7	6'-4	5	9	14'-9	6	9	4'-10	5	4.5	22'-5	14-16
17-19	5	12	8'-2	4	4.5	8'-2	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	9	21'-11	5	9	7'-3	5	12	5'-2	1'-10	3'-4	5	12	4'-11	1'-7	3'-4	5	9	14'-7	6	9	4'-11	5	4.5	21'-11	4	9	22'-5	5	9	7'-4	5	12	8'-2	1'-8	6'-6	5	12	8'-1	1'-7	6'-6	5	9	14'-10	6	9	4'-11	5	4.5	22'-5	17-19
20-22	4	12	8'-4	4	4.5	8'-4	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	9	21'-11	5	9	7'-6	5	12	5'-4	1'-11	3'-5	5	12	5'-0	1'-7	3'-5	6	12	14'-8	7	12	5'-2	6	4.5	21'-11	4	9	22'-5	5	9	7'-7	5	12	8'-4	1'-9	6'-7	5	12	8'-2	1'-7	6'-7	5	9	14'-10	6	9	5'-0	5	4.5	22'-5	20-22
23-25	4	12	8'-7	4	4.5	8'-7	4	9	16	4	9	9	5	12	18	4	18	16	4	12	22	4	18	16	4	9	21'-11	5	9	7'-10	5	12	5'-11	2'-5	3'-6	5	12	5'-6	2'-0	3'-6	6	12	14'-9	7	12	5'-4	6	4.5	21'-11	4	9	22'-5	5	9	7'-11	5	12	8'-6	1'-10	6'-8	5	12	8'-3	1'-7	6'-8	6	12	15'-0	7	12	5'-2	6	4.5	22'-5	23-25

DIMENSIONS

QUANTITIES

FILL	S	H	A	B	C	D	E	F	G	J	U	V	W	X	Y	Z	CONCRETE YD ³/FT SLAB	FLOOR	WALLS	TOTAL	STEEL LBS/FT
0	10	6	10.5	10.5	9	9	4.5	9	12	12	1'-10	11'-0	2'-7	2'-7	11'-3	1'-11	.779	.467	2.040	271.29
1	10	6	11	11	9	9	4.5	9	18	12	1'-11	6'-9	2'-4	2'-6	11'-3	1'-11	.813	.829	.467	2.109	276.37
2	10	6	8.5	10	9	9	4.5	9	12	12	1'-8	5'-8	2'-9	2'-8	4'-6	2'-0	.641	.759	.467	1.867	301.05
3	10	6	8	10	9	9	4.5	4.5	12	12	2'-6	4'-3	2'-3	2'-4	3'-10	2'-3	.607	.759	.467	1.833	245.61
4	10	6	8	10	9	9	4.5	4.5	12	12	2'-4	3'-11	2'-3	2'-5	3'-8	2'-3	.607	.759	.467	1.833	242.92
5-7	10	6	8	10	9	9	4.5	4.5	12	12	2'-5	3'-9	2'-6	2'-10	3'-6	2'-0	.607	.759	.467	1.833	259.42
8-10	10	6	8.5	10.5	9	9	4.5	9	12	12	2'-10	3'-7	2'-4	2'-6	3'-7	2'-4	.641	.794	.467	1.902	290.29
11-13	10	6	10	12	9	9	7.5	9	18	18	2'-6	3'-9	2'-5	2'-8	3'-9	2'-4	.744	.900	.467	2.111	298.26
14-16	10	6	11	13	9	9	4.5	9	12	12	2'-8	3'-8	2'-5	2'-8	3'-7	2'-5	.813	.970	.467	2.250	295.97
17-19	10	6	12.5	14.5	9	9	4.5	9	12	12	2'-9	3'-8	2'-6	2'-8	3'-8	2'-5	.916	1.075	.467	2.458	299.68
20-22	10	6	13.5	15.5	9	9	4.5	9	12	12	2'-8	3'-9	2'-7	2'-7	3'-8	2'-6	.985	1.145	.467	2.597	300.00
23-25	10	6	15	17	9	9	4.5	9	12	12	2'-7	3'-10	2'-8	2'-6	3'-10	2'-7	1.088	1.251	.467	2.806	309.34

* THESE DIMENSIONS ARE CORRECT FOR 38' LONG STANDARD SECTIONS ONLY. DIMENSIONS MUST BE RECALCULATED FOR ALL OTHER SECTION LENGTHS.

NOTES:

1. SEE DRAWING TWRCB-G1-87 FOR GENERAL INFORMATION, SPECIFICATIONS, AND DESIGN STRESSES.

BENT BAR DETAIL

BARS	D
4	3
5	3½
6	4½
7	5¼



NOTE:
ALL DIMENSIONS ARE OUT TO OUT.
D = PIN DIAMETER.





END SECTION - PLAN VIEW (KEYWAY NOT SHOWN)

NOTE: END SECTION DETAILS SHOWN ARE FOR A 15° SKEW BARREL.
USE FOR SKEWS OF 30° & 45° BY INCREASING
THE NUMBER OF TRANSVERSE REINFORCING BARS
REQUIRED TO BE CUT & RELOCATED.

NOTE : ALL LONGITUDINAL BARREL STEEL SHALL EXTEND AT LEAST TO THE BACKFACE OF PARAPET.



STANDARD SECTION PLAN VIEW

NOTE: TYPICAL FOR LENGTHS OF 38'.
(KEYWAY IS TO BE OMITTED WHEN
BELL JOINTS ARE USED)



TOP SLAB CONSTRUCTION JOINT DETAIL



BARREL SECTION

LATEST REVISION DATE : 12-5-96	APPROVED BY :	STANDARD DESIGN CULVERT BARREL DETAILS FOR TWIN REINFORCED CONCRETE BOX CULVERTS HIGHWAY DIVISION IOWA DEPARTMENT OF TRANSPORTATION JULY , 1987 TWRCB 10-6-87

REVISED: 8/89; KEYWAY NOTE & DETAIL ADDED. LONGITUDINAL BARREL STEEL NOTE ADDED.
REVISED: 12/96 ; KEYWAY NOTATION CHANGED, DOWEL BAR LENGTH CHANGED.
TWB106.SD1

XXXXXXXXXXSYSTEMTIME XXXXXXXXUSERNAME XXXXXXXXXX