



- LEGEND
- Traffic Sign
 - Flagger
 - Work Area
 - Type III Barricade
 - Direction of Traffic

SPEED LIMIT (mph)	A	F and G Range	F + G Max.
35 or less	250'	250'-3250'	3500'
40 - 45	350'	350'-3350'	3700'
50 or greater	500'	500'-3500'	4000'

① A vehicle with an amber revolving or an amber strobe light may be substituted for the Type III barricade.

② A second flagger shall be required:

If the flagger's view of approaching traffic in the open lane is less than 1/4 mile or the work site is in an area of restricted sight distance (such as a "No Passing" zone); or

If excessive traffic delays are encountered.

③ F and G distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, F and G distances may be varied within the limits of the table. Maximum movement can be achieved by setting one F or G value at the minimum and the other value at its maximum.

Possible Contract Items:

Traffic Control
Flaggers

Iowa Department of Transportation	REVISION	
	2	04-17-12
STANDARD ROAD PLAN	TC-212	
REVISIONS: No significant changes. Changed to color.		
 APPROVED BY DESIGN METHODS ENGINEER		
SPOT LOCATION LANE CLOSURE WITH FLAGGERS		