
PREQUALIFIED DRUMS

| <u>MANUFACTURER</u> | <u>PRODUCT NO.</u> | <u>MANUFACTURER RECOMMENDATION FOR BALLAST</u> |
|---------------------------------|--|---|
| Bent Mfg. Co. | Superdome Drum | Tire Ring Minimum 30 lbs. |
| Kimberly-Clark Global Safety | Highway Tech | 45-50 lb. (21-23 kg) sandbag used with plastic base. |
| Lakeside Plastics Inc. | “Director” | 40 lb. base |
| Plasticade Products | Rhino Channelizer Barrel Econocade II | 40lbs (Min) Base 40 lbs (Min) Base |
| Plastic Safety Systems, Inc. | Lifeguard, Lifeguard II | For 45 mph (72 km/h) and greater use two 25-lb. Tire collars For under 45 mph (72 km/h) use one 25-lb. tire collar. |
| Traffix Devices, Inc. | 1800 Generation IV 1800 Generation V | 50-55 lb. (23-25 kg) sandbag 50-55 lb. (23-25 kg) sand-filled base. |
| Work Area Protection Corp. | B-400 B-500 LC | 25-40 lb. (11.4-18.2 kg) sandbag 25-40 lb. (11.4-18.2 kg) rubber base 25 lb. (11.4 kg) base for speeds 45 mph (72 km/m) and under 35-40 lb. (15.9-18.2 kg) base for speeds greater than 45 mph (72 km/m) |