



LEGEND	
	Traffic Sign
	42" Channelizer
	Work Area
	Direction of Traffic

SPEED LIMIT (mph)	A	B	C ^②	T
35 or less	500'	250'	40'	100'
40 - 45	700'	350'	80' ^①	200'
50 or greater	1000'	500'	100' ^①	200'

When a pavement edge drop-off exists, install a SHOULDER DROP-OFF sign.

No pavement edge drop-offs greater than pavement depth will be allowed during non-working hours.

Shoulder edge drop-offs shall be mitigated according to Article 1107.08.L2 of the Standard Specifications.

^① When the length of a pavement edge drop-off is 1000 feet or less, the temporary fillet requirement of Article 1107.08 of the Standard Specifications does not apply.

Space devices at 40 feet.

^② For work areas less than 200 feet long, use channelizers spaced at 20 foot centers or use a vehicle with an amber Vehicle Warning Light.

Possible Contract Item:
Traffic Control

 STANDARD ROAD PLAN <small>REVISIONS: Adjusted circle note 2 to match other TCs. Changed standard note 2 from 10 inches to pavement depth. Corrected Article reference from K2 to L2.</small> <small>APPROVED BY DESIGN METHODS ENGINEER</small>	<small>REVISION</small> 5 10-16-12	
	TC-202	
	<small>SHEET 1 of 1</small>	
	SHOULDER CLOSURE (ONE LANE)	