

REVISED 09-14 - CHANGED REFERENCE TO THE J44-45-14 STANDARD FOR DIMENSION "B" INSTEAD OF J44-45-06 STANDARD.

EPOXY REINFORCING STEEL-TWO BARRIER RAILS

BRIDGE LENGTH				70'-0		80'-0		90'-0		100'-0		110'-0		120'-0		130'-0		140'-0		150'-0											
SECTION	BAR	LOCATION	SHAPE	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT										
STANDARD SECTION	5g1	VERTICAL		136	5'-11	839	156	5'-11	963	176	5'-11	1086	196	5'-11	1210	216	5'-11	1333	236	5'-11	1456	256	5'-11	1580	276	5'-11	1703	296	5'-11	1827	
	5f1	LONGITUDINAL		36	35'-1	1317	54	27'-5	1544	54	30'-9	1732	54	34'-1	1920	54	37'-5	2107	72	31'-2	2340	72	33'-8	2528	72	36'-2	2716	72	38'-8	2904	
	4 END SECTIONS @ 266 LBS.						1064			1064			1064			1064			1064			1064			1064			1064			1064
	(INCLUDE WITH SUPERSTRUCTURE REINFORCING)				TOTAL (LBS.)		3220	TOTAL (LBS.)		3571	TOTAL (LBS.)		3882	TOTAL (LBS.)		4194	TOTAL (LBS.)		4504	TOTAL (LBS.)		4860	TOTAL (LBS.)		5172	TOTAL (LBS.)		5483	TOTAL (LBS.)		5795



REINFORCING QUANTITIES SHOWN ARE BASED ON 45° SKEW BID LENGTHS.

STAINLESS STEEL REINFORCING STEEL-TWO BARRIER RAILS

BRIDGE LENGTH				70'-0		80'-0		90'-0		100'-0		110'-0		120'-0		130'-0		140'-0		150'-0											
SECTION	BAR	LOCATION	SHAPE	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT										
STANDARD SECTION	5g2	VERTICAL		136	6'-10	969	156	6'-11	1125	176	7'-1	1300	196	7'-4	1499	216	7'-6	1690	236	7'-9	1908	256	7'-11	2114	276	8'-2	2351	296	8'-5	2598	
	4 END SECTIONS @ 192 LBS.						768			768			768			768			768			768			768			768			768
	(INCLUDE WITH SUPERSTRUCTURE REINFORCING)				TOTAL (LBS.)		1737	TOTAL (LBS.)		1893	TOTAL (LBS.)		2068	TOTAL (LBS.)		2267	TOTAL (LBS.)		2458	TOTAL (LBS.)		2676	TOTAL (LBS.)		2882	TOTAL (LBS.)		3119	TOTAL (LBS.)		3366

REINFORCING QUANTITIES SHOWN ARE BASED ON 45° SKEW BID LENGTHS.

BENT BAR DETAILS



BRIDGE	"a"	LENGTH
70'	1'-2	6'-10
80'	1'-2 1/2	6'-11
90'	1'-3 1/2	7'-1
100'	1'-5	7'-4
110'	1'-6	7'-6
120'	1'-7 1/2	7'-9
130'	1'-8 3/4	7'-11
140'	1'-10	8'-2
150'	1'-11 1/2	8'-5

NOTE: ALL DIMENSIONS ARE OUT TO OUT.
"D"= PIN DIAMETER.

CONCRETE PLACEMENT SUMMARY

BRIDGE LENGTH		70'-0	80'-0	90'-0	100'-0	110'-0	120'-0	130'-0	140'-0	150'-0
STANDARD SECTION	* 2 x B @ 0.1052 CU. YDS. PER FT.	14.4	16.5	18.6	20.7	22.8	24.9	27.0	29.1	31.2
END SECTION	4 @ 0.65 CU. YDS.	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6
TOTAL (CU. YDS.)		17.0	19.1	21.2	23.3	25.4	27.5	29.6	31.7	33.8

* SEE J44-45-14 FOR DIMENSION "B".
CONCRETE QUANTITIES SHOWN ARE
BASED ON 45° SKEW BID LENGTHS.

CONCRETE BARRIER RAIL QUANTITIES

BRIDGE LENGTH		UNIT	70'-0	80'-0	90'-0	100'-0	110'-0	120'-0	130'-0	140'-0	150'-0
CONCRETE BARRIER RAILING	0° SKEW	L.F.	162.0	182.0	202.0	222.0	242.0	262.0	282.0	302.0	322.0
CONCRETE BARRIER RAILING	15° SKEW	L.F.	162.2	182.2	202.2	222.2	242.2	262.2	282.2	302.2	322.2
CONCRETE BARRIER RAILING	30° SKEW	L.F.	162.9	182.9	202.9	222.9	242.9	262.9	282.9	302.9	322.9
CONCRETE BARRIER RAILING	45° SKEW	L.F.	164.5	184.5	204.5	224.5	244.5	264.5	284.5	304.5	324.5

09-14 LATEST REVISION DATE APPROVED BY BRIDGE ENGINEER	 STANDARD DESIGN - 44' ROADWAY, 3 SPAN BRIDGES CONTINUOUS CONCRETE SLAB BRIDGES JULY, 2014
	BARRIER RAIL DETAILS
	J44-46-14