




PLAN VIEW OF BRIDGE BERM
(NON-BARNROOF FORESLOPE)

Grading Surface:
Refer to berm slope location table in project plans
for locations of A, B, W and possible other points.


- ① Variable slope.
- ② Bridge Berm slope may vary and is determined by the A and B points. Slope is normally 2.5:1 or flatter.
- ③ Refer to contract documents for limits of the slope protection.

 STANDARD ROAD PLAN	REVISION	3	10-21-14
	EW-202 SHEET 1 of 3		
REVISIONS: Changed label from Bridge Endpost to Bridge Rail End Section.			
 APPROVED BY DESIGN METHODS ENGINEER			
BRIDGE BERM GRADING WITHOUT RECOVERABLE SLOPE (NON-BARNROOF SECTION)			




SECTION C-C

- ② Bridge Berm slope may vary and is determined by the A and B points.
- ③ Refer to contract documents for limits of the slopeprotection.
- ④ Refer to **RK series** for longitudinal subgrade slope.
- ⑤ Temporary grading slope.
- g* = Pavement cross slope.




SECTION B-B





SECTION A-A

	REVISION	
	3	10-21-14
STANDARD ROAD PLAN	EW-202	
	SHEET 2 of 3	
REVISIONS: Changed label from Bridge Endpost to Bridge Rail End Section.		
APPROVED BY DESIGN METHODS ENGINEER		
BRIDGE BERM GRADING WITHOUT RECOVERABLE SLOPE (NON-BARNROOF SECTION)		

This image can be viewed in 3D on the the ERL or at our website <http://www.iowadot.gov/design/stdrdpln.htm>



This image can be viewed in 3D on the the ERL or at our website <http://www.iowadot.gov/design/stdrdpln.htm>

	REVISION	
	3	10-21-14
STANDARD ROAD PLAN	EW-202	
	SHEET 3 of 3	
REVISIONS: Changed label from Bridge Endpost to Bridge Rail End Section.		
		
APPROVED BY DESIGN METHODS ENGINEER		
BRIDGE BERM GRADING WITHOUT RECOVERABLE SLOPE (NON-BARNROOF SECTION)		