



When a shoulder drop-off of 6" or less exists, install a SHOULDER DROP-OFF sign, as shown.

When a shoulder drop-off greater than 6" exists, install a NO SHOULDER sign, as shown.

Where the length of a shoulder drop-off exceeds 1000 feet, construct a temporary fillet meeting the requirements of Article 1107.09 of the Standard Specifications.

Drop-offs greater than a nominal 10" will not be allowed during non-working hours.

- ① Spacing = 40' when shoulder drop-offs are present.
- ② For work areas less than 200' long, use channelizers spaced at 20' centers or use a vehicle with an amber revolving light or amber strobe light.

LEGEND

- † Traffic Sign
- 42" Channelizer or Vertical Panel
- Work Area
- ⇐ Direction of Traffic

SPEED LIMIT (mph)	A	B	T	C ^②
40 or less	500'	250'	100'	40'
45 - 50	700'	350'	200'	80' ①
55 - 60	1500'	500'	200'	100' ①
65 - 70	1500'	500'	230'	100' ①

Contract Item:
Traffic Control

 Iowa Department of Transportation	REVISION
	2 10-21-08
STANDARD ROAD PLAN	TC-402
REVISIONS: Modified speed limit table values and variables. Revorded notes.	SHEET 1 of 1
APPROVED BY DESIGN METHODS ENGINEER	
SHOULDER CLOSURE	