

TYP. HALF ELEVATION PIER CAP
(LOOKING PARALLEL TO ℄ ROADWAY)



TYP. HALF PLAN VIEW

NOTE: NUMBER OF PILES AND STIRRUPS SHOWN ARE FOR A 70'-0 BRIDGE. CAP DIMENSIONS ARE TYPICAL FOR ALL BRIDGES.



TYP. SECTION

GRADE TO BOTTOM OF CAP DIMENSION	
70'-0 BRIDGE	4'-8
80'-0 BRIDGE	4'-8¾
90'-0 BRIDGE	4'-9¾
100'-0 BRIDGE	4'-11
110'-0 BRIDGE	5'-0
120'-0 BRIDGE	5'-1½
130'-0 BRIDGE	5'-2¾
140'-0 BRIDGE	5'-4
150'-0 BRIDGE	5'-5½



PART PLAN

SHOWING TREATMENT OF 4 x ⅜ STRIP OF PREFORMED JOINT MATERIAL AT ENDS OF PIER CAP. NOTE THAT JOINT MATERIAL IS TO GO ALL THE WAY AROUND PIER CAP FOR SQUARE AND SKEWED BRIDGES.



PART SECT A-A



PART SECT B-B

LATEST REVISION DATE

APPROVED BY BRIDGE ENGINEER

Iowa Department of Transportation
Highway Division

STANDARD DESIGN - 30' ROADWAY, 3 SPAN BRIDGES

CONTINUOUS CONCRETE SLAB BRIDGES

NOVEMBER, 2006

NON-MONOLITHIC PIER CAP DETAILS ALL BRIDGES

SHEET 1 OF 2

J30-25-06