



**LEGEND**

- Traffic Sign
- Flagger
- 1050 mm Channelizer or Vertical Panel
- Type III Barricade
- Work Area
- Direction of Traffic

SPEED LIMIT (mph)	A (m)	B and C (m)	B + C Max. (m)	D (m)
35 or less	76	152-914	1067	30-60
40 - 50	107	213-914	1128	30-60
55	152	305-914	1219	60-91

- ① A vehicle with an amber revolving light or an amber strobe light may be substituted for the Type III barricade.
- ② B and C distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, B and C distances may be varied within the limits of the table. Maximum movement can be achieved by setting one B or C value at the minimum and the other value at its maximum.

Contract Items:  
Traffic Control  
Flaggers

All dimensions given in millimeters unless noted.

<b>M</b>	Iowa Department of Transportation	REVISION NEW   10-17-06
	<b>STANDARD ROAD PLAN</b> <small>REVISIONS: Replaces RS-3.</small>	<b>TC-213</b> SHEET 1 of 1
<b>METRIC VERSION</b>	 <small>APPROVED BY DESIGN METHODS ENGINEER</small>	
<b>LANE CLOSURE WITH FLAGGERS</b>		