



LEGEND

- ▬ Traffic Sign
- ✕ Drum
- 1050 mm Channellizer or Vertical Panel
- ▭ Arrow Panel
- Temporary Floodlighting
- ▨ Work Area
- ← Direction of Traffic

SPEED LIMIT (mph)	A (m)	B (m)	C (m)
55	235	100	17
65-70	277	119	20

When the Average Daily Traffic (ADT) exceeds 20,000 vehicles per day or when a traffic queue extends beyond the advanced signing RIGHT LANE CLOSED 4 MILES and RIGHT LANE CLOSED 2 MILES signs (W20-5) shall be placed on both sides of the roadway 6 kilometers and 3 kilometers in advance of the lane closure, respectively.

- ① For roadways with a posted speed limit of 60 mph or greater before road work:
Place SPEED LIMIT AHEAD sign and SPEED LIMIT 55 sign prior to the lane closure as shown. Place SPEED LIMIT 65 or 70 beyond the work area as shown.
All existing signs that conflict with 55 mph speed limit shall be removed or covered while 55 mph speed limit is in effect.
- ② For details, see RD-65.

- Contract Items:
- Traffic Control
 - Painted Pavement Markings
 - Painted Symbols and Legends
 - Pavement Markings Removed
 - Symbols and Legends Removed
 - Temporary Barrier Rail
 - Temporary Floodlighting

Tabulations:
108-33
108-27

All dimensions given in millimeters unless noted.

M METRIC VERSION	 Iowa Department of Transportation	REVISION NEW 10-17-06
		STANDARD ROAD PLAN REVISIONS: Replaces RS-80.
	<i>Deanna Mayfield</i> APPROVED BY DESIGN METHODS ENGINEER	
	LANE CLOSURE WITH TBR	