



Two Way Traffic symbol and DO NOT PASS signs shall be placed alternately on both sides of the roadway at a maximum of one-half mile intervals for both directions of travel. The motorists shall always have signs in sight.

- See RD-65 for details.
- See Typical 9015 for details.
- Speed Limit signs shall be spaced at one-mile intervals.
- An additional supplemental plate with the message NEXT X MILES shall be installed on the Two Way Traffic symbol sign assembly on the right side of the roadway to inform the motorist of the remaining length of two lane traffic. The number shall be to the nearest whole-mile increment. This shall be required for both directions of traffic.

Contract Items:
 Traffic Control
 Safety Closures
 Raised Pavement Markings
 Painted Pavement Markings
 Painted Symbols and Legends
 Pavement Markings Removed
 Temporary Attenuators
 Temporary Floodlighting

Tabulations: 108-13A, 108-22, 108-29, 108-30, 108-33, 108-27

All dimensions given in millimeters unless noted.

M METRIC VERSION	 Iowa Department of Transportation	REVISION NEW 10-17-06
		TC-61(2)
	STANDARD ROAD PLAN	
	<i>Deanna Mayfield</i> APPROVED BY DESIGN METHODS ENGINEER	
TWO-LANE, TWO-WAY OPERATION		

SHEET 2 of 4