



LEGEND

- 42" Channelizer or Vertical Panel
- × Drum
- ↑ Traffic Sign
- ▨ Work Area
- ← Direction of Traffic
- ▬ Type III Barricade
- ▭▭▭ Arrow Panel

SPEED LIMIT (mph)	A	B	C	D	E
25 or less	300'	125'	40'	50'	25'
30 - 35	500'	245'	80'	50'	35'
40 - 50	700'	540'	200'	100'	45'
55	1000'	770'	280'	100'	55'

- ① Two drums shall be placed in the closed lane(s) at 500 ft. intervals. Where core-out, holes, or uncured concrete exists within the work area, an additional pair of drums shall be placed just ahead of each.
- ② The arrow panel shall be placed behind the channelizing devices and as close to the beginning of the taper as practical.
- ③ A vehicle with an amber revolving light or amber strobe light may be substituted for the Type III barricade.

Contract Item:
Traffic Control

 Iowa Department of Transportation	REVISION
	NEW 10-17-06
STANDARD ROAD PLAN	TC-429
REVISIONS: New.	SHEET 1 of 1
 APPROVED BY DESIGN METHODS ENGINEER	
CLOSURE OF CONTINUOUS TWO WAY LEFT TURN LANE AND/OR ADJACENT LANE	