



SPEED LIMIT (mph)	A	B and C (3)	B + C Max.
35 or less	75 m	75-1000 m	1075 m
40 - 50	105 m	105-1020 m	1125 m
55	150 m	150-1070 m	1220 m

- ① A vehicle with an amber revolving light or an amber strobe light may be substituted for the Type III barricade.
- ② A second flagger shall be required:  
 If the flagger's view of approaching traffic in the open lane is less than 400 meters or the work site is in an area of restricted sight distance (such as a "No Passing" zone); or  
 If excessive traffic delays are encountered.
- ③ B and C distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, B and C distances may be varied within the limits of the table. Maximum movement can be achieved by setting one B or C value at the minimum and the other value at its maximum.

Contract Items:  
 Traffic Control  
 Flaggers

All dimensions given in millimeters unless noted.

<b>M</b> <b>METRIC VERSION</b>	 <b>Iowa Department of Transportation</b>	REVISION NEW   10-17-06
		<b>STANDARD ROAD PLAN</b> <small>REVISIONS: Replaces RS-20.</small>
	 <small>APPROVED BY DESIGN METHODS ENGINEER</small>	
	<b>SPOT LOCATION LANE CLOSURE WITH FLAGGERS</b>	

**TC-212**  
 SHEET 1 of 1