

**APPROVED SOURCES  
 CONCRETE SEALERS FOR NON-TRAFFIC AREAS**

\*All surfaces to be sealed must be sound, clean and DRY.

<u>MANUFACTURER</u>	<u>BRAND NAME</u>	<u>COVERAGE RATE</u>	<u>MIN. SURFACE TEMP. °C (°F)</u>
Conspec	Spec-Seal	1 or 2 coats 2.5 m <sup>2</sup> /L (100 ft. <sup>2</sup> /gal.)	10 (50)
International Chem-Crete	Pavix CCC 100	3.7 to 4.9 m <sup>2</sup> /L (150 to 200 ft. <sup>2</sup> /gal.)	4 (40)
L & M Construction Chemicals Inc.	Pentox 50	2 coats 1st coat 4.91 m <sup>2</sup> /L (200 ft. <sup>2</sup> /gal.)  2nd coat 7.36 m <sup>2</sup> /L (300 ft. <sup>2</sup> /gal.)	10 (50)
Poly-Carb, Inc.	Mark-124, Mark-145	2 coats 1st coat Mark-124 2.70 m <sup>2</sup> /L (110 ft. <sup>2</sup> /gal.)  2nd coat Mark-145 2.95 m <sup>2</sup> /L (120 ft. <sup>2</sup> /gal.)	7 (45)
Poly-Carb, Inc.	Mark-87	2 coats 1st coat Mark-87 2.95 m <sup>2</sup> /L (120 ft. <sup>2</sup> /gal.)  2nd coat Mark-87 2.45 m <sup>2</sup> /L (100 ft. <sup>2</sup> /gal.)	10 (50)
Sika Chemical Company	Sikadur 21 Lo-Mod LV	3.07 m <sup>2</sup> /L (125 ft. <sup>2</sup> /gal.)	4 (40)

---

<b><u>MANUFACTURER</u></b>	<b><u>BRAND NAME</u></b>	<b><u>COVERAGE RATE</u></b>	<b><u>MIN. SURFACE TEMP. °C (°F)</u></b>
Star, Inc. (McConnell & Assoc.)	Macro-Dect	7.36 m <sup>2</sup> /L (80 ft. <sup>2</sup> /gal.)	4 (40)
Steelcote Mfg. Company	PE-50 Penetrating Sealer	1.96 m <sup>2</sup> /L (80 ft. <sup>2</sup> /gal.)	4 (40)
TK Products	TK-2671 Penetrating Sealer	2 coats 9.82 m <sup>2</sup> /L (400 ft. <sup>2</sup> /gal.) each coat	4 (40)
Unitex	Bridge Seal	1 coat 2.45 m <sup>2</sup> /L (100 ft. <sup>2</sup> /gal.)	4 (40)
Viking Paints, Inc.	Paulco TE-3008-1	2 coats 9.82 m <sup>2</sup> /L (400 ft. <sup>2</sup> /gal.) each coat	4 (40)