



Where shoulder drop-offs (2 inches or greater) exist:

- a. The SHOULDER DROP-OFF sign shall follow the ROAD WORK AHEAD sign. When the drop-off exceeds 6", the SHOULDER DROP-OFF sign shall be replaced by a NO SHOULDER sign.
- b. A temporary fillet meeting the requirements of Article 1107.09 shall be required when the length of shoulder drop-off is 1000 feet or greater.
- c. No drop-offs greater than a nominal 10" shall be allowed during nonworking hours.

Contract Item:

Traffic Control

LEGEND

- ▬ Traffic Sign
- 42" Channelizer or Vertical Panel
- ▨ Work Area
- ← Direction of Traffic

SPEED LIMIT (mph)	A	B	C	D	E ①
35 or less	500'	250'	100'	20'	40'
40 - 50	700'	350'	200'	40'	40'
55	1000'	500'	200'	40'	80' ②

① Work areas less than 200 feet long without shoulder drop-offs shall be delineated by channelizing devices at 20-foot spacing or by a vehicle with an amber revolving light or amber strobe light.

② Spacing = 40' when shoulder drop-offs are present.

	REVISION	
	NEW	10-17-06
<b>STANDARD ROAD PLAN</b>	<b>TC-202</b>	
REVISIONS: Replaces RS-2.	SHEET 1 of 1	
 APPROVED BY DESIGN METHODS ENGINEER		
<b>SHOULDER CLOSURE</b>		