



- LEGEND**
- Traffic Sign
 - Flagger
 - Work Area
 - Type III Barricade
 - Direction of Traffic

SPEED LIMIT (mph)	A	B and C ^③	B + C Max.
35 or less	250'	250'-3250'	3500'
40 - 50	350'	350'-3350'	3700'
55	500'	500'-3500'	4000'

- ① A vehicle with an amber revolving light or an amber strobe light may be substituted for the Type III barricade.
- ② A second flagger shall be required:
 If the flagger's view of approaching traffic in the open lane is less than 1/4 mile or the work site is in an area of restricted sight distance (such as a "No Passing" zone); or
 If excessive traffic delays are encountered.
- ③ B and C distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, B and C distances may be varied within the limits of the table. Maximum movement can be achieved by setting one B or C value at the minimum and the other value at its maximum.

Contract Items:
 Traffic Control
 Flaggers

	REVISION
	NEW 10-17-06
STANDARD ROAD PLAN	TC-212
REVISIONS: Replaces RS-20.	SHEET 1 of 1
 APPROVED BY DESIGN METHODS ENGINEER	
SPOT LOCATION LANE CLOSURE WITH FLAGGERS	