



Where shoulder drop-offs (50 millimeters or greater) exist:

- The SHOULDER DROP-OFF sign shall follow the ROAD WORK AHEAD sign. When the drop-off exceeds 150 mm, the SHOULDER DROP-OFF sign shall be replaced by a NO SHOULDER sign.
- A temporary fillet meeting the requirements of Article 1107.09 shall be required when the length of shoulder drop-off is 300 meters or greater.
- No drop-offs greater than a nominal 250 mm shall be allowed during nonworking hours.

Contract Item:  
Traffic Control

All dimensions given in millimeters unless noted.

LEGEND

- Traffic Sign
- 1050 mm Channelizer or Vertical Panel
- Work Area
- Direction of Traffic

SPEED LIMIT (mph)	A (m)	B (m)	C (m)	D (m)	E (m)
35 or less	150	75	30	6	12
40 - 50	300	150	60	12	12
55 - 70	450	150	80	12	24

① Work areas less than 60 meters long without shoulder drop-offs shall be delineated by channelizing devices at 6-meter spacing or by a vehicle with an amber revolving light or amber strobe light.

② Spacing = 12 meters when shoulder drop-offs are present.

<b>M</b>		REVISION NEW   10-17-06
		<b>TC-402</b>
<b>METRIC VERSION</b>	<b>STANDARD ROAD PLAN</b>	
	<small>REVISIONS: Replaces RS-62.</small>  <small>APPROVED BY DESIGN METHODS ENGINEER</small>	
	<b>SHOULDER CLOSURE</b>	