


END ROAD WORK
G20-2A
1200 X 600

END ROAD WORK
G20-2A
1200 X 600



LEGEND

- Traffic Sign
- Drum
- 1050 mm Channelizer or Vertical Panel
- Type III Barricade
- Arrow Panel
- Work Area
- Direction of Traffic

SPEED LIMIT (mph)	A (m)	B (m)	C (m)	D (m)	E (m)
25 or less	91	38	30	8	12
30 - 35	150	76	38	11	24
40 - 45	213	165	82	14	24
50 - 55	305	201	100	17	24

Contract Item:
Traffic Control

All dimensions given in millimeters unless noted.

When this layout is used during nighttime hours and the width of the traffic lanes are 3.4 meters or less, the Contractor shall use tubular markers to separate head-to-head traffic.

- ① A pair of drums shall be placed in the closed lane at 150 meter intervals. When core-outs, holes or uncured concrete exist within the work area, an additional pair of drums shall be placed just ahead of each.
- ② A vehicle with an amber revolving light or amber strobe light may be substituted for the Type III Barricade.

M METRIC VERSION	 Iowa Department of Transportation	REVISION NEW 10-17-06
		TC-423 SHEET 1 of 1
	STANDARD ROAD PLAN	
	<i>Deanna Mayfield</i> APPROVED BY DESIGN METHODS ENGINEER	
CLOSURE OF TWO ADJACENT LANES ON UNDIVIDED HIGHWAY		