



**LEGEND**

- 1050 mm Channelizer or Vertical Panel
- ✕ Drum
- ⚡ Traffic Sign
- ▨ Work Area
- ← Direction of Traffic
- ⚡ Type III Barricade
- ▤ Arrow Panel

SPEED LIMIT (mph)	A	B	C	D	E
25 or less	90 m	38 m	12 m	15 m	8 m
30 - 35	150 m	74 m	24 m	15 m	11 m
40 - 50	210 m	162 m	60 m	30 m	14 m
55	300 m	231 m	84 m	30 m	17 m

This layout may be used to close both inside travel lanes simultaneously.

- ① Two drums shall be placed in the closed lane(s) at 150 meter intervals. Where core-out, holes, or uncured concrete exists within the work area, an additional pair of drums shall be placed just ahead of each.
- ② The arrow panel shall be placed behind the channelizing devices and as close to the beginning of the taper as practical.
- ③ A vehicle with an amber revolving light or amber strobe light may be substituted for the Type III barricade.

Contract Item:  
Traffic Control

All dimensions given in millimeters unless noted.

<b>M</b> <b>METRIC VERSION</b>	 Iowa Department of Transportation	REVISION NEW   10-17-06
		<b>TC-429</b>
	<b>STANDARD ROAD PLAN</b>	
	REVISIONS: New. <i>Deanna Mayfield</i> APPROVED BY DESIGN METHODS ENGINEER	

**CLOSURE OF CONTINUOUS TWO WAY LEFT TURN LANE AND/OR ADJACENT LANE**