

## INDEX FOR H44-14 STANDARDS:

H44-01-14	INDEX SHEET
H44-01A-14	GENERAL NOTES
H44-02-14	GENERAL INFORMATION
H44-03-14	SUPERSTRUCTURE DETAILS
H44-04-14	SUPERSTRUCTURE DETAILS-MISC.
H44-05-14	ABUTMENT DETAILS FOR 0° SKEW, A & B BEAMS
H44-06-14	ABUTMENT DETAILS FOR 0° SKEW, C BEAMS
H44-14-14	LONGITUDINAL SECTION FOR 0° SKEW, A & B BEAMS
H44-08-14	LONGITUDINAL SECTION FOR 0° SKEW, C BEAMS
H44-09-14	SUPERSTRUCTURE DETAILS FOR 0° SKEW
H44-10-14	DECK & ABUTMENT REINF. FOR 0° SKEW
H44-11-14	ABUTMENT DETAILS FOR 15° SKEW, A & B BEAMS
H44-12-14	ABUTMENT DETAILS FOR 15° SKEW, C BEAMS
H44-13-14	LONGITUDINAL SECTION FOR 15° SKEW, A & B BEAMS
H44-14-14	LONGITUDINAL SECTION FOR 15° SKEW, C BEAMS
H44-15-14	SUPERSTRUCTURE DETAILS FOR 15° SKEW
H44-16-14	DECK & ABUTMENT REINF. FOR 15° SKEW
H44-17-14	ADDITIONAL QUANTITIES FOR 15° SKEW
H44-18-14	ABUTMENT DETAILS FOR 30° SKEW, A & B BEAMS
H44-19-14	ABUTMENT DETAILS FOR 30° SKEW, C BEAMS
H44-20-14	LONGITUDINAL SECTION FOR 30° SKEW, A & B BEAMS
H44-21-14	LONGITUDINAL SECTION FOR 30° SKEW, C BEAMS
H44-22-14	SUPERSTRUCTURE DETAILS FOR 30° SKEW
H44-23-14	DECK & ABUTMENT REINF. FOR 30° SKEW
H44-24-14	ADDITIONAL QUANTITIES FOR 30° SKEW
H44-25-14	A BEAM DETAILS
H44-26-14	A BEAM DETAILS
H44-27-14	B BEAM DETAILS
H44-28-14	B BEAM DETAILS
H44-29-14	C BEAM DETAILS
H44-30-14	C BEAM DETAILS
H44-31-14	INTERMEDIATE STEEL DIAPHRAGMS
H44-32-14	BARRIER RAIL DETAILS 1 OF 3
H44-33-14	BARRIER RAIL DETAILS 2 OF 3
H44-34-14	BARRIER RAIL DETAILS 3 OF 3
H44-35-14	OPEN RAIL DETAILS 1 OF 2
H44-36-14	OPEN RAIL DETAILS 2 OF 2
H44-36A-14	OPEN RAIL DETAILS 2A OF 2
H44-37-14	PIER BEARING DETAILS

## INDEX FOR H44-14 STANDARDS (CONT'D.):

H44-38-14	PILE BENT PIERS FOR 0° SKEW
H44-39-14	PILE BENT PIERS FOR 0° SKEW
H44-40-14	PILE BENT PIERS HP14 PILES FOR 0° SKEW
H44-41-14	PILE BENT PIERS HP14 PILES FOR 0° SKEW
H44-42-14	PILE BENT PIERS FOR 15° SKEW
H44-43-14	PILE BENT PIERS FOR 15° SKEW
H44-44-14	PILE BENT PIERS HP14 PILES FOR 15° SKEW
H44-45-14	PILE BENT PIERS HP14 PILES FOR 15° SKEW
H44-46-14	PILE BENT PIERS FOR 30° SKEW
H44-47-14	PILE BENT PIERS FOR 30° SKEW
H44-48-14	PILE BENT PIERS HP14 PILES FOR 30° SKEW
H44-49-14	PILE BENT PIERS HP14 PILES FOR 30° SKEW
H44-50-14	TEE PIER CAP AND COLUMN, 0° SKEW
H44-51-14	TEE PIER CAP AND COLUMN, 0° SKEW
H44-52-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H44-53-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H44-54-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H44-55-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H44-56-14	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=16' TO 24'
H44-57-14	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=25' TO 40'
H44-58-14	TEE PIER CAP AND COLUMN, 15° SKEW
H44-59-14	TEE PIER CAP AND COLUMN, 15° SKEW
H44-60-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H44-61-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H44-62-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H44-63-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H44-64-14	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=16' TO 24'
H44-65-14	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=25' TO 40'
H44-66-14	TEE PIER CAP AND COLUMN, 30° SKEW
H44-67-14	TEE PIER CAP AND COLUMN, 30° SKEW
H44-68-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H44-69-14	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H44-70-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H44-71-14	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H44-72-14	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=16' TO 24'
H44-73-14	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=25' TO 40'
H44-74-14	SUBDRAIN DETAILS
H44-75-14	WING ARMORING DETAILS, A & B BEAMS
H44-76-14	WING ARMORING DETAILS, C BEAMS
H44-77-14	ABUTMENT BACKFILL DETAIL, A & B BEAMS - 0° SKEW
H44-78-14	ABUTMENT BACKFILL DETAIL, A & B BEAMS - SKEWED
H44-79-14	ABUTMENT BACKFILL DETAIL, C BEAMS - 0° SKEW
H44-80-14	ABUTMENT BACKFILL DETAIL, C BEAMS - SKEWED

STRUCTURAL RESISTANCE LEVEL-1 (SRL-1) REPLACES THE 50 TON STEEL PILE DESIGNATION.

STRUCTURAL RESISTANCE LEVEL 2 (SRL-2) REPLACES THE 75 TON STEEL PILE DESIGNATION.

FOR MORE INFORMATION ON STRUCTURAL RESISTANCE LEVELS (SRL-1 & SRL-2), SEE THE BRIDGE DESIGN MANUAL, LOCATED ON THE IOWA DEPARTMENT OF TRANSPORTATIONS, OFFICE OF BRIDGES AND STRUCTURES, WEB SITE.

LATEST REVISION DATE

*Thomas E. M. Donnell*  
APPROVED BY BRIDGE ENGINEER



STANDARD DESIGN - 44' ROADWAY, THREE SPAN BRIDGE  
**PRETENSIONED PRESTRESSED  
CONCRETE BEAM BRIDGES**  
SEPTEMBER, 2014

INDEX SHEET

H44-01-14