VARIABLE DIMENSIONS AND QUANTITIES FOR BARREL SECTIONS

BAR LIST

	a1			a2			b1		b2		e1		e2		f1		f2		k1		k2		k4					k5					k6			k7			k9			m1			m2			m4					m5					m6			m7			m9			
FILL	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	NO.	SIZE	SP	LENGTH	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	h	v	SIZE	SP	LENGTH	SIZE	SP	LENGTH	SIZE	SP	LENGTH	FILL
0	4	6	13'-8	7	9	13'-8	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	8'-0	4	12	5'-1	1'-11	3'-2	5	12	5'-1	1'-11	3'-2	4	12	22'-8	4	12	4'-10	4	4.5	22'-8	4	12	23'-2	5	12	6'-9	5	12	14'-2	2'-0	12'-2	5	12	14'-0	1'-10	12'-2	4	9	23'-2	4	9	3'-11	4	4.5	23'-2	0
1	4	6	13'-9	7	9	13'-9	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	7'-11	4	12	5'-3	1'-11	3'-4	5	12	5'-3	1'-11	3'-4	4	12	22'-8	5	12	5'-3	4	4.5	22'-8	4	12	23'-2	5	12	6'-11	5	12	14'-0	1'-11	12'-1	5	12	13'-11	1'-10	12'-1	5	12	15'-11	5	12	4'-0	5	4.5	23'-2	1
2	4	9	13'-6	7	9	13'-6	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	6	12	8'-1	6	15	6'-11	3'-0	3'-11	6	15	6'-1	2'-2	3'-11	4	9	17'-2	5	9	5'-5	4	4.5	22'-8	4	9	23'-2	5	9	6'-10	6	15	14'-2	2'-8	11'-6	6	15	13'-6	2'-0	11'-6	5	9	15'-6	5	9	4'-2	5	4.5	23'-2	2
3	5	12	13'-5	7	9	13'-5	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	4	9	22'-8	4	9	6'-6	5	12	5'-9	2'-10	2'-11	5	12	4'-11	2'-0	2'-11	5	12	15'-6	5	12	4'-7	5	4.5	22'-8	4	12	23'-2	5	12	7'-0	5	12	14'-11	2'-10	12'-1	5	12	13'-11	1'-10	12'-1	4	9	15'-3	5	9	4'-8	4	4.5	23'-2	3
4	5	12	13'-5	7	9	13'-5	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	4	12	22'-8	5	12	7'-0	6	18	5'-11	2'-10	3'-1	6	18	5'-3	2'-2	3'-1	5	12	15'-2	5	12	4'-5	5	4.5	22'-8	4	12	23'-2	5	12	6'-11	6	18	14'-3	2'-0	12'-3	4	9	15'-1	5	9	4'-8	4	4.5	23'-2	4
5-7	5	12	13'-5	7	9	13'-5	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	4	12	22'-8	5	12	6'-11	5	12	5'-8	2'-9	2'-11	5	12	4'-11	2'-0	2'-11	4	9	14'-10	5	9	4'-11	4	4.5	22'-8	5	12	23'-2	5	12	6'-2	5	12	14'-7	2'-6	12'-1	5	12	13'-11	1'-10	12'-1	5	9	15'-0	5	9	4'-2	5	4.5	23'-2	5-7
8-10	6	9	13'-6	7	9	13'-6	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	6'-2	6	18	5'-10	2'-8	3'-2	6	18	5'-4	2'-2	3'-2	5	9	14'-9	5	9	4'-4	5	4.5	22'-8	5	12	23'-2	5	12	6'-5	6	18	14'-11	2'-7	12'-4	6	12	15'-2	6	12	4'-6	6	4.5	23'-2	8-10
11-13	4	9	13'-8	7	9	13'-8	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	6'-5	7	18	6'-9	2'-9	4'-0	7	18	6'-7	2'-7	4'-0	6	12	14'-11	6	12	4'-8	6	4.5	22'-8	4	9	23'-2	5	9	7'-1	7	18	15'-1	2'-8	12'-5	7	18	14'-10	2'-5	12'-5	5	9	15'-2	6	9	4'-10	5	4.5	23'-2	11-13
14-16	5	12	13'-11	7	9	13'-11	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	6'-6	6	12	6'-6	2'-5	4'-1	6	12	6'-2	2'-1	4'-1	6	12	14'-11	6	12	4'-9	6	4.5	22'-8	4	9	23'-2	5	9	7'-1	6	12	14'-2	2'-4	11'-10	6	12	13'-10	2'-0	11'-10	7	15	15'-4	7	15	4'-10	7	7.5	23'-2	14-16
17-19	5	12	14'-1	7	9	14'-1	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	5	12	22'-8	5	12	6'-9	6	12	5'-9	2'-4	3'-5	6	12	5'-5	2'-0	3'-5	7	15	15'-1	7	15	5'-0	7	7.5	23'-2	7	15	23'-2	6	12	7'-4	6	12	15'-0	2'-4	12'-8	6	12	14'-8	2'-0	12'-8	7	15	15'-4	7	15	5'-0	7	7.5	23'-2	17-19
20-22	5	12	14'-3	7	9	14'-3	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	4	9	22'-8	5	9	7'-4	6	12	5'-10	2'-4	3'-6	6	12	5'-6	2'-0	3'-6	5	9	14'-11	6	9	5'-0	5	4.5	22'-8	4	9	23'-2	5	9	7'-6	6	12	15'-0	2'-3	12'-9	6	12	14'-9	2'-0	12'-9	7	15	15'-4	7	15	5'-0	7	7.5	23'-2	20-22
23-25	6	12	14'-6	7	9	14'-6	4	9	32	4	9	17	5	12	18	4	18	16	4	12	22	4	18	16	4	9	22'-8	5	9	7'-8	6	12	6'-0	2'-4	3'-8	6	12	5'-8	2'-0	3'-8	5	9	15'-0	6	9	5'-2	5	4.5	22'-8	4	9	23'-2	5	9	7'-10	6	12	15'-2	2'-4	12'-10	6	12	14'-10	2'-0	12'-10	7	15	15'-4	7	15	5'-1	7	7.5	23'-2	23-25

DIMENSIONS

QUANTITIES

FILL	S	H	A	B	C	D*	E*	F*	G*	J*	U	V	W	X	Y	Z	CONCRETE YD ³FT SLAB	FLOOR	WALLS	TOTAL	STEEL LBS/FT
0	10	12	10.5	11	12	6	4.5	9	12	12	1'-10	11'-4	2'-5	2'-6	11'-7	2'-0	.817	.859	1.291	2.967	351.16
1	10	12	11	11.5	12	6	4.5	9	12	12	1'-11	11'-4	2'-7	2'-5	4'-4	2'-0	.852	.896	1.291	3.039	351.79
2	10	12	9	10	12	9	4.5	7.5	12	12	1'-9	5'-10	2'-8	2'-5	3'-11	2'-1	.710	.787	1.291	2.788	386.50
3	10	12	8	10	12	9	4.5	9	12	12	2'-6	4'-2	2'-3	2'-4	3'-8	2'-4	.639	.787	1.291	2.717	339.82
4	10	12	8	10	12	9	4.5	9	12	12	2'-3	3'-10	2'-2	2'-4	3'-6	2'-4	.639	.787	1.291	2.717	337.58
5-7	10	12	8	10	12	9	4.5	9	12	12	2'-4	3'-6	2'-5	2'-10	3'-5	2'-1	.639	.787	1.291	2.717	349.97
8-10	10	12	8.5	11	12	9	4.5	9	12	12	2'-10	3'-5	2'-2	2'-9	3'-7	2'-3	.675	.859	1.291	2.825	396.32
11-13	10	12	9.5	12	12	9	4.5	9	12	12	2'-10	3'-7	2'-4	2'-6	3'-7	2'-5	.746	.932	1.291	2.969	409.84
14-16	10	12	11	13.5	12	9	4.5	9	12	18	2'-11	3'-7	2'-4	2'-8	3'-9	2'-5	.852	1.041	1.291	3.184	422.05
17-19	10	12	12	14.5	12	9	4.5	9	18	18	2'-10	3'-9	2'-6	2'-6	3'-9	2'-6	.923	1.113	1.291	3.327	428.61
20-22	10	12	13	15.5	12	9	4.5	9	12	18	2'-7	3'-7	2'-6	2'-7	3'-9	2'-6	.994	1.186	1.291	3.471	428.26
23-25	10	12	14.5	17	12	9	4.5	9	12	18	2'-6	3'-8	2'-7	2'-5	3'-9	2'-6	1.101	1.295	1.291	3.687	447.13

* THESE DIMENSIONS ARE CORRECT FOR 38'-0 LONG STANDARD SECTIONS ONLY. DIMENSIONS MUST BE RECALCULATED FOR ALL OTHER SECTION LENGTHS.

NOTES:

1. SEE DRAWING TWRCB-GI-87 FOR GENERAL INFORMATION, SPECIFICATIONS, AND DESIGN STRESSES.

BENT BAR DETAIL

BARS	D
4	3
5	3½
6	4½
7	5¼

NOTE:
ALL DIMENSIONS ARE OUT TO OUT.
D = PIN DIAMETER.



END SECTION - PLAN VIEW (KEYWAY NOT SHOWN)

NOTE: END SECTION DETAILS SHOWN ARE FOR A 15° SKEW BARREL. USE FOR SKEWS OF 30° & 45° BY INCREASING THE NUMBER OF TRANSVERSE REINFORCING BARS REQUIRED TO BE CUT & RELOCATED.

NOTE : ALL LONGITUDINAL BARREL STEEL SHALL EXTEND AT LEAST TO THE BACKFACE OF PARAPET.



STANDARD SECTION PLAN VIEW

NOTE: TYPICAL FOR LENGTHS OF 38'.
(KEYWAY IS TO BE OMITTED WHEN BELL JOINTS ARE USED)



TOP SLAB CONSTRUCTION JOINT DETAIL



BARREL SECTION

LATEST REVISION DATE : 12-5-96	APPROVED BY :	STANDARD DESIGN
		CULVERT BARREL DETAILS
		FOR TWIN REINFORCED CONCRETE BOX CULVERTS
		HIGHWAY DIVISION
		IOWA DEPARTMENT OF TRANSPORTATION
		JULY , 1987 — TWRCB 10-12-87

REVISED: 8/89; KEYWAY NOTE & DETAIL ADDED, LONGITUDINAL BARREL STEEL NOTE ADDED.
REVISED: 12/96 ; KEYWAY NOTATION CHANGED, DOWEL BAR LENGTH CHANGED.
TWB10T2.2S01

XXXXXXXXXXSYSTEMTIME XXXXXXXUSERNAME XXXXXXXXXX