

REVISED 05-13 - THE GENERAL NOTES AND SPECIFICATIONS MOVED TO STANDARD SHEET H30-01A-06. SRL NOTATION ADDED.

**INDEX FOR H24-06 STANDARDS:**

H24-01-06	INDEX SHEET
H24-01A-06	GENERAL NOTES
H24-02-06	GENERAL INFORMATION
H24-03-06	SUPERSTRUCTURE DETAILS
H24-04-06	SUPERSTRUCTURE DETAILS-MISC.
H24-05-06	ABUTMENT DETAILS FOR 0° SKEW, A & B BEAMS
H24-06-06	ABUTMENT DETAILS FOR 0° SKEW, C BEAMS
H24-07-06	LONGITUDINAL SECTION FOR 0° SKEW, A & B BEAMS
H24-08-06	LONGITUDINAL SECTION FOR 0° SKEW, C BEAMS
H24-09-06	SUPERSTRUCTURE DETAILS FOR 0° SKEW
H24-10-06	DECK & ABUTMENT REINF. FOR 0° SKEW
H24-11-06	ABUTMENT DETAILS FOR 15° SKEW, A & B BEAMS
H24-12-06	ABUTMENT DETAILS FOR 15° SKEW, C BEAMS
H24-13-06	LONGITUDINAL SECTION FOR 15° SKEW, A & B BEAMS
H24-14-06	LONGITUDINAL SECTION FOR 15° SKEW, C BEAMS
H24-15-06	SUPERSTRUCTURE DETAILS FOR 15° SKEW
H24-16-06	DECK & ABUTMENT REINF. FOR 15° SKEW
H24-17-06	ADDITIONAL QUANTITIES FOR 15° SKEW
H24-18-06	ABUTMENT DETAILS FOR 30° SKEW, A & B BEAMS
H24-19-06	ABUTMENT DETAILS FOR 30° SKEW, C BEAMS
H24-20-06	LONGITUDINAL SECTION FOR 30° SKEW, A & B BEAMS
H24-21-06	LONGITUDINAL SECTION FOR 30° SKEW, C BEAMS
H24-22-06	SUPERSTRUCTURE DETAILS FOR 30° SKEW
H24-23-06	DECK & ABUTMENT REINF. FOR 30° SKEW
H24-24-06	ADDITIONAL QUANTITIES FOR 30° SKEW
H24-25-06	ABUTMENT DETAILS FOR 45° SKEW, A & B BEAMS
H24-26-06	ABUTMENT DETAILS FOR 45° SKEW, C BEAMS
H24-27-06	LONGITUDINAL SECTION FOR 45° SKEW, A & B BEAMS
H24-28-06	LONGITUDINAL SECTION FOR 45° SKEW, C BEAMS
H24-29-06	SUPERSTRUCTURE DETAILS FOR 45° SKEW
H24-30-06	DECK & ABUTMENT REINF. FOR 45° SKEW
H24-31-06	ADDITIONAL QUANTITIES FOR 45° SKEW
H24-32-06	A BEAM DETAILS
H24-33-06	B BEAM DETAILS
H24-34-06	C BEAM DETAILS
H24-35-06	C BEAM DETAILS
H24-36-06	C BEAM DETAILS
H24-37-06	C BEAM DETAILS
H24-38-06	INTERMEDIATE STEEL DIAPHRAGMS
H24-39-06	OPEN RAIL DETAILS, 1 OF 2
H24-40-06	OPEN RAIL DETAILS, 2 OF 2
H24-41-06	PIER BEARING DETAILS



**INDEX FOR H24-06 STANDARDS (CONT'D.):**

H24-42-06	PILE BENT PIERS FOR 0° SKEW
H24-43-06	PILE BENT PIERS-HP14 PILES FOR 0° SKEW
H24-44-06	PILE BENT PIERS FOR 15° SKEW
H24-45-06	PILE BENT PIERS HP14 PILES FOR 15° SKEW
H24-46-06	PILE BENT PIERS FOR 30° SKEW
H24-47-06	PILE BENT PIERS HP14 PILES FOR 30° SKEW
H24-48-06	PILE BENT PIERS FOR 45° SKEW
H24-49-06	PILE BENT PIERS HP14 PILES FOR 45° SKEW
H24-50-06	TEE PIER CAP AND COLUMN, 0° SKEW
H24-51-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H24-52-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H24-53-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H24-54-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H24-55-06	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=16' TO 24'
H24-56-06	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=25' TO 40'
H24-57-06	TEE PIER CAP AND COLUMN, 15° SKEW
H24-58-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H24-59-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H24-60-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H24-61-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H24-62-06	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=16' TO 24'
H24-63-06	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=25' TO 40'
H24-64-06	TEE PIER CAP AND COLUMN, 30° SKEW
H24-65-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H24-66-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H24-67-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H24-68-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H24-69-06	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=16' TO 24'
H24-70-06	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=25' TO 40'
H24-71-06	TEE PIER CAP AND COLUMN, 45° SKEW
H24-72-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H24-73-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H24-74-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H24-75-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H24-76-06	TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=16' TO 24'
H24-77-06	TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=25' TO 40'
H24-78-06	SUBDRAIN DETAILS
H24-79-06	WING ARMORING DETAILS, A & B BEAMS
H24-80-06	WING ARMORING DETAILS, C BEAMS
H24-81-06	ABUTMENT BACKFILL DETAIL, A & B BEAMS - 0° SKEW
H24-82-06	ABUTMENT BACKFILL DETAIL, A & B BEAMS - SKEWED
H24-83-06	ABUTMENT BACKFILL DETAIL, C BEAMS - 0° SKEW
H24-84-06	ABUTMENT BACKFILL DETAIL, C BEAMS - SKEWED

STRUCTURAL RESISTANCE LEVEL-1 (SRL-1) REPLACES THE 50 TON STEEL PILE DESIGNATION.

STRUCTURAL RESISTANCE LEVEL-2 (SRL-2) REPLACES THE 75 TON STEEL PILE DESIGNATION.

FOR MORE INFORMATION ON STRUCTURAL RESISTANCE LEVELS (SRL-1 & SRL-2), SEE THE BRIDGE DESIGN MANUAL, LOCATED ON THE IOWA DEPARTMENT OF TRANSPORTATIONS, OFFICE OF BRIDGES AND STRUCTURES, WEBSITE.

LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER	 <b>Iowa Department of Transportation</b> <i>Highway Division</i>
	STANDARD DESIGN - 24' ROADWAY, THREE SPAN BRIDGE <b>PRETENSIONED PRESTRESSED          CONCRETE BEAM BRIDGES</b> DECEMBER, 2006	
	<b>INDEX SHEET</b>	<b>H24-01-06</b>