

REVISED 05-13 - THE GENERAL NOTES AND SPECIFICATIONS MOVED TO STANDARD SHEET H40-01A-06. SRL NOTATION ADDED.

INDEX FOR H40-06 STANDARDS:

H40-01-06 INDEX SHEET
H40-01A-06 GENERAL NOTES
H40-02-06 GENERAL INFORMATION
H40-03-06 SUPERSTRUCTURE DETAILS
H40-04-06 SUPERSTRUCTURE DETAILS-MISC.
H40-05-06 ABUTMENT DETAILS FOR 0° SKEW, A & B BEAMS
H40-06-06 ABUTMENT DETAILS FOR 0° SKEW, C BEAMS
H40-07-06 LONGITUDINAL SECTION FOR 0° SKEW, A & B BEAMS
H40-08-06 LONGITUDINAL SECTION FOR 0° SKEW, C BEAMS
H40-09-06 SUPERSTRUCTURE DETAILS FOR 0° SKEW
H40-10-06 DECK & ABUTMENT REINF. FOR 0° SKEW
H40-11-06 ABUTMENT DETAILS FOR 15° SKEW, A & B BEAMS
H40-12-06 ABUTMENT DETAILS FOR 15° SKEW, C BEAMS
H40-13-06 LONGITUDINAL SECTION FOR 15° SKEW, A & B BEAMS
H40-14-06 LONGITUDINAL SECTION FOR 15° SKEW, C BEAMS
H40-15-06 SUPERSTRUCTURE DETAILS FOR 15° SKEW
H40-16-06 DECK & ABUTMENT REINF. FOR 15° SKEW
H40-17-06 ADDITIONAL QUANTITIES FOR 15° SKEW
H40-18-06 ABUTMENT DETAILS FOR 30° SKEW, A & B BEAMS
H40-19-06 ABUTMENT DETAILS FOR 30° SKEW, C BEAMS
H40-20-06 LONGITUDINAL SECTION FOR 30° SKEW, A & B BEAMS
H40-21-06 LONGITUDINAL SECTION FOR 30° SKEW, C BEAMS
H40-22-06 SUPERSTRUCTURE DETAILS FOR 30° SKEW
H40-23-06 DECK & ABUTMENT REINF. FOR 30° SKEW
H40-24-06 ADDITIONAL QUANTITIES FOR 30° SKEW
H40-25-06 ABUTMENT DETAILS FOR 45° SKEW, A & B BEAMS
H40-26-06 ABUTMENT DETAILS FOR 45° SKEW, C BEAMS
H40-27-06 LONGITUDINAL SECTION FOR 45° SKEW, A & B BEAMS
H40-28-06 LONGITUDINAL SECTION FOR 45° SKEW, C BEAMS
H40-29-06 SUPERSTRUCTURE DETAILS FOR 45° SKEW
H40-30-06 DECK & ABUTMENT REINF. FOR 45° SKEW
H40-31-06 ADDITIONAL QUANTITIES FOR 45° SKEW
H40-32-06 A BEAM DETAILS
H40-33-06 A BEAM DETAILS
H40-34-06 B BEAM DETAILS
H40-35-06 B BEAM DETAILS
H40-36-06 C BEAM DETAILS
H40-37-06 C BEAM DETAILS
H40-38-06 INTERMEDIATE STEEL DIAPHRAGMS
H40-39-06 BARRIER RAIL DETAILS 1 OF 3
H40-40-06 BARRIER RAIL DETAILS 2 OF 3
H40-41-06 BARRIER RAIL DETAILS 3 OF 3
H40-42-06 OPEN RAIL DETAILS 1 OF 2
H40-43-06 OPEN RAIL DETAILS 2 OF 2
H40-44-06 PIER BEARING DETAILS



INDEX FOR H40-06 STANDARDS (CONT'D.):

H40-45-06 PILE BENT PIERS FOR 0° SKEW
H40-46-06 PILE BENT PIERS FOR 0° SKEW
H40-47-06 PILE BENT PIERS HP14 PILES FOR 0° SKEW
H40-48-06 PILE BENT PIERS FOR 15° SKEW
H40-49-06 PILE BENT PIERS FOR 15° SKEW
H40-50-06 PILE BENT PIERS HP14 PILES FOR 15° SKEW
H40-51-06 PILE BENT PIERS FOR 30° SKEW
H40-52-06 PILE BENT PIERS FOR 30° SKEW
H40-53-06 PILE BENT PIERS HP14 PILES FOR 30° SKEW
H40-54-06 PILE BENT PIERS FOR 45° SKEW
H40-55-06 PILE BENT PIERS FOR 45° SKEW
H40-56-06 PILE BENT PIERS HP14 PILES FOR 45° SKEW
H40-57-06 TEE PIER CAP AND COLUMN, 0° SKEW
H40-58-06 TEE PIER CAP AND COLUMN, 0° SKEW
H40-59-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H40-60-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H40-61-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H40-62-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H40-63-06 TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=16' TO 24'
H40-64-06 TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=25' TO 40'
H40-65-06 TEE PIER CAP AND COLUMN, 15° SKEW
H40-66-06 TEE PIER CAP AND COLUMN, 15° SKEW
H40-67-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H40-68-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H40-69-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H40-70-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H40-71-06 TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=16' TO 24'
H40-72-06 TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=25' TO 40'
H40-73-06 TEE PIER CAP AND COLUMN, 30° SKEW
H40-74-06 TEE PIER CAP AND COLUMN, 30° SKEW
H40-75-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H40-76-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H40-77-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H40-78-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H40-79-06 TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=16' TO 24'
H40-80-06 TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=25' TO 40'
H40-81-06 TEE PIER CAP AND COLUMN, 45° SKEW
H40-82-06 TEE PIER CAP AND COLUMN, 45° SKEW
H40-83-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H40-84-06 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H40-85-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H40-86-06 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H40-87-06 TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=16' TO 24'
H40-88-06 TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=25' TO 40'
H40-89-06 SUBDRAIN DETAILS
H40-90-06 WING ARMORING DETAILS, A & B BEAMS
H40-91-06 WING ARMORING DETAILS, C BEAMS
H40-92-06 ABUTMENT BACKFILL DETAIL, A & B BEAMS - 0° SKEW
H40-93-06 ABUTMENT BACKFILL DETAIL, A & B BEAMS - SKEWED
H40-94-06 ABUTMENT BACKFILL DETAIL, C BEAMS - 0° SKEW
H40-95-06 ABUTMENT BACKFILL DETAIL, C BEAMS - SKEWED

STRUCTURAL RESISTANCE LEVEL-1 (SRL-1) REPLACES THE 50 TON STEEL PILE DESIGNATION.

STRUCTURAL RESISTANCE LEVEL-2 (SRL-2) REPLACES THE 75 TON STEEL PILE DESIGNATION.

FOR MORE INFORMATION ON STRUCTURAL RESISTANCE LEVELS (SRL-1 & SRL-2), SEE THE BRIDGE DESIGN MANUAL, LOCATED ON THE IOWA DEPARTMENT OF TRANSPORTATIONS, OFFICE OF BRIDGES AND STRUCTURES, WEBSITE.

05-13 LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER	 Iowa Department of Transportation <i>Highway Division</i> STANDARD DESIGN - 40' ROADWAY, THREE SPAN BRIDGE PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGES AUGUST, 2009
INDEX SHEET		H40-01-06